

QUICK DISCONNECT CHARGE FITTING SELECTION CHART

HYSON



Gas Spring Model		Quick Disconnect Charge Fitting
TNK 200*	T2SS2-24	T2-770-T3 (M6 side or base port)
TNK 400	T2SL-170	
TNK 400 HS	T3-170	
TNKS 1000	T3-320	
TNKS 2400	T3-350	
T2-50	T3-500	
T2-90	T3-750	
T2-180	T3-1000	
T2SC-420	T3-1500	
T2SC-740	T3-2400	
T2L-300	T3T-350	
T2LS-300	T3T-500	
T2SS2-16	T3T-750	



Gas Spring Model		Quick Disconnect Charge Fitting
TNKS 4200	T3T-1500	T2-770-G1/8-P (BSPP 1/8 port)
TNKS 6600	T4-1000	
NP-500	T4-2400	
NP-750	T4-4200	
NP-1500	T4-6600	
NP-3000	T4-9500	
NP-5000	LCF/P-750	
NP-7500	LCF/P-1500	
NP-10000	LCF/P-3000	
T2SC-1800	LCF/P-5000	
T2SC-2900	LCF/P-7500	
T2SC-4700	CS2-1500	
T2SC-7500	CS2-3000	
T2SC-11800	CS2-5000	
T2SC-18300	CS2-7500	
T2SLM-300	SRS-750	
T3-4200	SRS-1500	
T3-6600	SRS-3000	
T3-9500	SRS-5000	
T3-20000		



Gas Spring Model		Quick Disconnect Charge Fitting
TNK1*	T2L-3000*	T2-770-4 (7/16"-20 port)
TNKB 1000	T2L-5000*	
TNKB 2400	T2-750P	
TNKB 4200	T2B-1500	
TNKB 6600	T2B-3000	
TNKT 1000	T2B-5000	
TNKT 2400	T2-7500	
TNKT 4200	T3T-1000	
TNKT 6600	T3T-2400	
T2L-500	T3T-4200	
T2L-750	T3T-6600	
T2L-1500*	T3T-9500	



Gas Spring Model	Quick Disconnect Charge Fitting
T2-250*	T2-770-M6 (M6 rod port)
T2LS-250*	
T2LS-500*	
T2LS-750*	
T2SC-1000	



Gas Spring Model	Quick Disconnect Charge Fitting
TNK400**	11-770-0705 MTY (3/8"-32 port)
TNK400 HS**	



Gas Spring Model	Quick Disconnect Charge Fitting
TNK 3"	T2-770-4-L (7/16"-20 port)
TNK 5.5"	
TNK 9"	

For Control Panels, Pressure Monitors and other accessories



11-770-2700
(1/4" NPT Female)



11-700-8555
(1/2"-20 O-ring)



11-770-0705
(1/4" NPT Male)



*Obsolete gas spring models
**Old style gas springs. New style uses T2-770-T3.

Notes: The charge fitting is needed only when charging self-contained gas springs. It is not needed for a hoses or baseplate system.

Check individual product catalogs for minimum and maximum charging pressures.

