



Hydraulic LIFT TABLES

FOR LIGHT INDUSTRIAL AND COMMERCIAL USE

MOST STANDARD DESIGNS ARE ALSO AVAILABLE IN ELECTRIC-HYDRAULIC AND AIR-OPERATED VERSIONS

GENERAL SPECIFICATIONS OF 200 LB., 300 LB., AND 400 LB. CAPACITY TABLES

1. THE LIGHT DUTY 200 LB., 300 LB. AND 400 LB. CAPACITY TABLES HAVE SIMPLE TELESCOPING SUPPORTS.
2. CASTERS, HYDRAULIC LIFT-UNITS, AND FLOOR LOCKS (IF PROVIDED) ARE BOLTED FOR EASY REPLACEMENT.
3. RUGGED, REPAIRABLE HYDRAULIC LIFT-UNITS.
4. ALL STEEL CONSTRUCTION WITH DURABLE ENAMEL FINISH.
5. QUALITY ENGINEERED AND BACKED BY 40 YEARS OF PROVEN RELIABILITY.
6. ALL U.S.A. MADE



**200 LB. CAPACITY
MODEL HT-200-R
Hand Operated**



**300 LB. CAPACITY
MODEL HT-300-FR**

200 LB. CAPACITY MODELS					Shipping Wt. Lbs.	
Model No.	Size	Low Ht.	Lift	Max. Ht.	Hand	Foot
HT-200-R	16" x 16"	29"	15"	44"	52	53
HT-203-R	16" x 16"	27"	13"	40"	51	52
HT-201-R	16" x 16"	25"	11"	36"	50	51
HT-209-R	16" x 16"	23"	9"	32"	49	50
Top & Base 3/16" Steel Top Rotates 360°						
(4) Swivel 2" dia. Rubber Casters but no Floor Lock supplied on 200 lb. capacity tables.						



**200 LB. CAPACITY
MODEL HT-200-FR
Foot Operated**

300 LB. CAPACITY MODELS					Shipping Wt. Lbs.	
Model No.	Size	Low Ht.	Lift	Max. Ht.	Foot Operated	
HT-300-FR	18" x 18"	30"	18"	48"	135	
HT-318-FR	18" x 18"	28"	18"	46"	131	
HT-316-FR	18" x 18"	26"	16"	42"	128	
HT-314-FR	18" x 18"	24"	14"	38"	124	
HT-312-FR	18" x 18"	22"	12"	34"	121	
Top & Base are 3/8" Thick Steel						
(2) Rigid, (2) Swivel 3 1/2" dia. Rubber Casters, (1) Floor Lock supplied on 300 lb. tables. Option available for Composition or Polyurethane Wheels only.						



**400 LB. CAPACITY
MODEL HT-400-FR**

400 LB. CAPACITY MODELS					Shipping Wt. Lbs.	
Model No.	Size	Low Ht.	Lift	Max. Ht.	Foot Operated	
HT-400-FR	18" x 24"	30"	18"	48"	119	
HT-416-FR	18" x 24"	28"	16"	44"	115	
HT-414-FR	18" x 24"	26"	14"	40"	112	
HT-412-FR	18" x 24"	24"	12"	36"	108	
Top & Base—12 Ga. Steel Reinforced Construction						
(2) Rigid, (2) Swivel 5" dia. Rubber-Tired Casters, and (1) Floor Lock supplied on 400 lb. capacity tables. Option available for Composition, Steel or Polyurethane Wheels.						



LEXCO

Hydraulic LIFT TABLES

MOST STANDARD DESIGNS ARE ALSO AVAILABLE IN ELECTRIC-HYDRAULIC AND AIR-OPERATED VERSIONS

GENERAL SPECIFICATIONS OF ALL LEXCO 500# CAP. THRU 60,000# CAP. TABLES

1. TRIPLE TELESCOPING GUIDE SUPPORTS FOR GREATER STABILITY AT MAXIMUM LIFT, AND FOR YEARS OF EXTRA WEAR.
2. LARGE EASY ROLLING CASTERS, AND FLOOR LOCKS ARE BOLTED FOR EASY REPLACEMENT.
3. RUGGED, FAST—ELEVATING, REPAIRABLE HYDRAULIC LIFT-UNITS ARE ALSO BOLTED FOR EASY REPLACEMENT..
4. ALL STEEL CONSTRUCTION WITH DURABLE ENAMEL FINISH.
5. QUALITY ENGINEERED AND BACKED BY 40 YEARS OF PROVEN RELIABILITY.
6. ALL U.S.A. MADE



**MODEL HT-500-FR
500 LB. CAPACITY**



**All 20" x 30" Drop-Base
Models—500 lb. to 2000 lb. Capacity**

500 LB. CAPACITY MODELS					Description			Shipping Wt. Lbs.		
Model No.	Size	Low Ht.	Lift	Max. Ht.	Foot Operated Standard	Electric Hydraulic Option	Air Operated Option	Foot	Elec.	Air
HT-500-FR	20" x 30"	30"	18"	48"	Top & Base—12 Ga. Steel Reinforced Construction			142	219	182
HT-2388-05-FR	20" x 30"	28"	18"	46"				173	257	182
HT-2368-05-FR	20" x 30"	26"	18"	44"				180	264	180
HT-2346-05-FR	20" x 30"	24"	16"	40"				176	260	176
HT-2324-05-FR	20" x 30"	22"	14"	36"				170	254	170
HT-2302-05-FR	20" x 30"	20"	12"	32"				164	248	164

(2) Rigid, (2) Swivel 5" dia. Rubber-Tired Casters and (1) Floor Lock supplied on 500 lb. capacity tables. Option available for Composition, Steel or Polyurethane Wheels.



Hydraulic LIFT TABLES



MOST STANDARD DESIGNS ARE ALSO AVAILABLE IN ELECTRIC-HYDRAULIC AND AIR-OPERATED VERSIONS



MODEL HT-2338-2F



**All 30" x 30"
2000 Lb. Capacity
Drop-Base Models**



MODEL HT-3338-2F

2,000 LB. CAPACITY MODELS					Description			Shipping Wt. Lbs.		
Model No.	Size	Low Ht.	Lift	Max. Ht.	Foot Operated	Electric Hydraulic	Air Operated	Foot	Elec.	Air
					Standard	Option	Option			
HT-2338-2F	20" x 30"	30"	18"	48"	All 2000 Lb. Capacity Models are constructed from 1/4" Steel—Reinforced Top & Base			215	294	320
HT-2388-2F	20" x 30"	28"	18"	46"				216	302	328
HT-2368-2F	20" x 30"	26"	18"	44"				224	309	—
HT-2346-2F	20" x 30"	24"	16"	40"				220	297	—
HT-2324-2F	20" x 30"	22"	14"	36"				213	290	—
HT-2302-2F	20" x 30"	20"	12"	32"				208	285	—
HT-3338-2F	30" x 30"	30"	18"	48"				276	355	381
HT-3388-2F	30" x 30"	28"	18"	46"				274	354	389
HT-3368-2F	30" x 30"	26"	18"	44"				284	364	—
HT-3346-2F	30" x 30"	24"	16"	40"				280	360	—
HT-3324-2F	30" x 30"	22"	14"	36"				274	354	—
HT-3302-2F	30" x 30"	20"	12"	32"				268	348	—

(2) Rigid, (2) Swivel 5" dia. Steel Casters and (1) Floor Lock supplied on 2000 lb. capacity tables. Option available for Composition or Polyurethane Wheels.

2,000 LB. CAPACITY MODELS					Shipping Wt. Lbs.		
Model No.	Size	Low Ht.	Lift	Max. Ht.	Standard Foot	Option Elec.	Option Air
HT-3438-24	30" x 48"	30"	18"	48"	460	539	565
HT-3488-24	30" x 48"	28"	18"	46"	472	551	587
HT-3468-24	30" x 48"	26"	18"	44"	482	561	—
HT-3446-24	30" x 48"	24"	16"	40"	478	557	—
HT-3424-24	30" x 48"	22"	14"	36"	472	551	—
HT-3402-24	30" x 48"	20"	12"	32"	466	545	—

(4) 5" dia. Steel Swivel Casters—(2) Floor Locks supplied on above tables. Option available for Composition or Polyurethane Wheels.



MODEL HT-3438-24