

H&O DIE SUPPLY, INC.

sales@hodie.com • 800-222-5441

True Swivel Head
Miter to 60°
13" Capacity

MODEL

1316S

Miter Head Bandsaw



Standard Infeed
Conveyor Not Shown



Manufactured in the United States of America

www.hodie.com

Wellsaw®

Built better to work stronger and last longer

7200 Interstate 20 • Kennedale, TX 76060

1316S

Model 1316S Miter Head Bandsaw



Standard Features

- Saw Head Swivels on Precision Ball Bearings
- Miter to 60° – No Need to Swivel the Stock
- Large Protractor for Accurate Angle Selection
- 5' x 18" Infeed Roller Conveyor
- Spring-Loaded Carbide Guides with Rollers
- Combination Reduction Gearbox and Ring & Pinion Blade Drive
- Baldor® Motor
 - 3hp Motor 3 Phase TEFC
 - 2hp Single Phase ODP
- Infinitely Variable Blade Speeds
- Variable Hydraulic Downfeed Control
- Work Light with Transformer
- Rite-Tension® Blade Tensioning Device
- Wet Cutting System with Full Surround Pan
- Powered Blade Brush
- 110 Volts at Controls
- Magnetic Starter with Overload and Undervoltage Protection
- Precision Ground Bed and Vise Jaws
- Quick Acting Vise
- Adjustable Stock Stop/Back Gauge
- Auto Shut-Off at End of Cut
- OSHA Blade Guarding
- Tiger-Tooth® Bi-Metal Blade
- Coolant for Initial Start-Up

Specifications

Capacity	Round Rectangular
@ 0° (90°)	13" 13"H x 16"W
@ 45°	11-1/2" 13"H x 11-1/2"W
@ 60°	8" 8-1/2"H x 8"W
Blade Size	1" x .035" x 12'6" (150")
Blade Speeds	Infinitely Variable 70-375 SFPM
Blade Guides	Carbide Guides with Rollers
Blade Tension	Manual Rite-Tension®
Electrical Options	115-208-230/60/1 208-230-460/60/3
Coolant System	Tank Capacity 8 Gallons Submersible Pump 115V/.6 Amp/3 GPM
Vise Control	Quick Acting/Manual Screw
Feed Rate Control	Variable Hydraulic
Band Wheels	15" Diameter Cast Iron
Stock Stop Projection	25"
Bed Height	35"
Floor Area	90"W x 76"L
Shipping Weight	1600 Lbs.

Available Factory Installed Options

- PLC Controlled Semi-Automatic Operation
 - Blade Break/Stall Switch
 - Flush Hose with 8.5 GPM Pump
 - Powered Frame Raise and/or Powered Vise
 - Laser Line Pointer
 - Casters (Set of 4, 2 Locking)
 - NFPA Electrics (with Disconnect)
 - Stock Stand, 18"
 - 5' Non-Powered Roller Conveyor
 - 10' Non-Powered Conveyors
- Please Contact Our Factory for Additional Options

