



16645 Heimbach Road
 Three Rivers, MI 49093
 Phone 269-279-5123
 Fax 269-279-6337
www.wfwells.com

2013

W.F. WELLS MODEL F-16-2**Specifications**

| | | |
|--------------------------|---|-----------------------|
| Capacity..... | Rectangular at 90° 16" High x 20" Wide, Round at 90° 16" Diameter | |
| | Rectangular at 45° 16" High X 9" Wide, Round at 45° 9" Diameter | |
| Weight Capacity..... | 5,000 lbs | |
| Blade Speed | 60-425 SFPM | |
| Blade Size | 1¼" X .042" X 15' | |
| Blade Guide..... | Rollers and Carbide Side Blocks | |
| Blade Tension..... | Hydraulic | |
| Bandwheel Size | 20" | <u>Voltage</u> |
| Vise | Full Stroke Hydraulic, 8-1/2" | 208-60-3 |
| Blade Drive | 7½ HP, AC Vector Drive | 230-60-3 |
| Sawing Force..... | 0-750 lbs | 460-60-3 |
| Coolant Capacity | 15 Gallons | 575-60-3 (5 HP) |
| Hydraulic Capacity | 20 Gallons | |
| Hydraulic Drive | 2 HP Motor | |
| Work Height..... | 26" | |
| Shipping Weight..... | 2,450 lbs | |
| Electrics | Wired to NFPA 79 Machine Tool Standards | |
| Machine Dimensions..... | 97" Length x 49" Width x 83" Height | |

OPTIONAL FACTORY INSTALLED ACCESSORIES**Description**

Automatic Length Stop Assembly
 Discharge Worktable, 20" W x 48" L with Stock Stop
 Work Light, Wired In
 Blade Break/Stall Switch
 Hydraulic Chip Conveyor
 Hydraulic Holddown, Saw Vise
 Hydraulic Swivel Base with Miter Vise (See M-16-2)
 Hydraulic Powered Conveyor 21" X 10'
 High Speed Drive & Guides (1" Blade) 400-3000 SFPM
 Hour Meter
 Free Standing Roller Stock Conveyors, 6" Centers:
 18" X 5' X 2,500 lbs Cap. Distributed Weight
 18" X 10' X 5,000 lbs Cap. Distributed Weight
 21" X 5' X 5,000 lbs Cap. Distributed Weight
 21" X 10' X 10,000 lbs Cap. Distributed Weight

Consult Factory For Additional Accessories

*Prices and specifications subject to change without notice

| |
|--------------------|
| MADE IN USA |
|--------------------|