



16645 Heimbach Road
 Three Rivers, MI 49093
 Phone: (269) 279-5123
 Fax: (269) 279-6337
www.wfwells.com

W.F. WELLS MODEL H-2024-1**Specifications**

Capacity.....	Rectangular at 90° 20" High x 24" Wide, Round at 90° 20" Diameter	
Weight Capacity.....	5,000 lbs	
Blade Speed.....	60-500 SFPM	
Blade Size.....	1¼" X .042" X 17' -8"	
Blade Guide.....	Rollers and Carbide Side Blocks	
Blade Tension.....	Manual with Indicator	
Bandwheel Size.....	20"	
Vise.....	Manual, 15"	<u>Voltage</u>
Blade Drive.....	7½ HP, AC Vector Drive	208-60-3
Sawing Force.....	30-120 lbs	230-60-3
Coolant Capacity.....	15 Gallons	460-60-3
Hydraulic Capacity.....	¾ Gallon	575-60-3
Hydraulic Drive.....	1/3 HP Motor	
Work Height.....	26"	
Shipping Weight.....	2,800 lbs	
Electrics.....	Wired to NFPA 79 Machine Tool Standards	
Shipping Dimensions.....	101"L x 40"W x 86"H	

OPTIONAL FACTORY INSTALLED ACCESSORIES**Description**

Automatic Length Stop Assembly
 Discharge Worktable, 20" W x 48" L with Stock Stop
 Discharge Worktable, 24" W x 48" L with Stock Stop
 Work Light, Wired In
 Air Vise, Manual
 Air Holddown, Manual
 Blade Break/Stall Switch
 Electronic Chip Conveyor, Auger Style
 High Speed Drive & Guides (1" Blade) 400-3000 SFPM
 Free Standing Roller Stock Conveyors, 6" Centers
 21"X 5' X 5,000 lbs Cap. Distributed Weight
 21" X 10' X 10,000 lbs Cap. Distributed Weight
 24" X 5' X 5,000 lbs Cap. Distributed Weight
 24" X 10' X 10,000 lbs Cap. Distributed Weight
 Electronic Powered Conveyor 21" X 10'
 24" Powered Conveyor

Consult Factory for Additional Accessories

*Prices and specifications subject to change without notice

