



16645 Heimbach Road
Three Rivers, MI 49093
Phone 269-279-5123
Fax 269-279-6337
www.wfwells.com

2013

W.F. WELLS MODEL W-10-1

Specifications

Capacity	Rectangular at 90° 10" High x 17" Wide, Round at 90° 10" Dia. Rectangular at 45° 10" High X 7½" Wide, Round at 45° 7½" Dia.	
Weight Capacity	5,000 lbs	
Blade Speed	60-425 SFPM	
Blade Size	1" X .035" X 11'-11"	
Sawing Feed	Variable, Hydraulic	
Blade Guide	Carbide Block	
Blade Tension	Manual with Indicator	
Bandwheel Size	14½"	<u>Voltage</u>
Vise	Manual	208-60-3
Blade Drive	5 HP, 3ph, AC Vector Drive	230-60-3
Sawing Force	30-120 lbs	460-60-3
Coolant Capacity	15 Gallons	575-60-3 (2HP)
Hydraulic Capacity	¾ Gallon	
Hydraulic Drive	⅓ HP Motor	
Work Height	26"	
Shipping Weight	1,400 lbs	
Electrics	Wired to NFPA 79 Machine Tool Standards	
Machine Dimensions	97" Length x 49" Width x 65" Height	

OPTIONAL FACTORY INSTALLED ACCESSORIES

Description

- Casters
- Automatic Length Stop Assembly
- Discharge Worktable, 20" W x 48" L with Stock Stop
- Work Light, Wired In
- Manual Air Vise
- Blade Break/Stall Switch
- Stock Stand, 6" Wide (Heavy duty)
- Stock Stand, 12" Wide (Heavy duty)
- High Speed AC Drive (400-3000 SFPM)
- Free Standing Roller Stock Conveyors, 6" Centers:
- 18" X 5' X 2,500 lbs Cap. Distributed Weight
- 18" X 10' X 5,000 lbs Cap. Distributed Weight

Consult Factory For Additional Accessories

*Prices and specifications subject to change without notice

