



16645 Heimbach Road
 Three Rivers, MI 49093
 Phone 269-279-5123
 Fax 269-279-6337
www.wfwells.com

2013

W.F. WELLS MODEL W-10-2**Specifications**

Capacity.....	Rectangular @ 90° 10" High x 17" Wide, Round @ 90° 10" Dia. Rectangular @ 45° 10" High X 7½" Wide Round @ 45° 7½" Dia.	
Weight Capacity.....	5,000 lbs	
Blade Speed.....	60-500 SFPM	
Blade Size.....	1" X .035" X 11'-11"	
Blade Guide.....	Carbide Block	
Blade Tension.....	Hydraulic, Console Controlled	
Bandwheel Size.....	14½"	<u>Voltage</u>
Vise.....	Hydraulic, Full Stroke	208-60-3
Blade Drive.....	5 HP, AC Vector Drive	230-60-3
Sawing Force.....	Hydraulic 0-750 lbs	460-60-3
Coolant Capacity.....	15 Gallons	575-60-3 (2HP)
Hydraulic Capacity.....	20 Gallons	
Hydraulic Drive.....	2 HP Motor	
Work Height.....	26"	
Shipping Weight.....	1,975 lbs	
Electrics.....	Wired to NFPA 79 Machine Tool Standards	
Machine Dimensions.....	97" Length x 49" Width x 65" Height	

OPTIONAL FACTORY INSTALLED ACCESSORIES**Description**

Discharge Worktable, 20" W x 48" L with Stock Stop
 Work Light, Wired In
 Automatic Length Stop Assembly
 Blade Break/Stall Switch
 Hydraulic Chip Conveyor, Auger Style
 Hydraulic Holddown, Saw Vise
 Stock Stand, 6" Wide (Heavy Duty)
 Stock Stand, 12" Wide (Heavy Duty)
 High Speed Drive & Guide 400-3000 SFPM, ¾" Blade
 Free Standing Roller Stock Conveyors, 6" Centers:
 18" X 5' X 2,500 lbs Cap. Distributed Weight
 18" X 10' X 5,000 lbs Cap. Distributed Weight

Consult Factory For Additional Accessories

*Prices and specifications subject to change without notice

MADE IN USA