H&O DIE SUPPLY, INC.

13" x 18" Capacity PLC Controlled, Full Cycle **Semi-Automatic Operation**



formerly model 1118 SA



Welsaw

Built better to work stronger and last longer

www.hodie.com

Manufactured in the United States of America

7200 Interstate 20 • Kennedale, TX 76060





Standard Features

PLC Controlled, Full Cycle Semi-Automatic Operation

Variable Hydraulic Feed Rate Control

Spring-Loaded Carbide Guides with Rollers

Combination Reduction Gearbox and Perimeter Ring Gear Blade Drive

Didue Dilve

Baldor® Motor 3hp Motor 3 Phase TEFC

2hp Single Phase ODP

Infinitely Variable Blade Speeds

Rite-Tension® Blade Tensioning Device

Wet Cutting System

Powered Blade Brush

110 Volts at Controls

Overload and Undervoltage Protection

Precision Ground Bed and Vise Jaws

Quick Acting Vise/Air Powered

Adjustable Stock Stop

Auto Shut-Off at End of Cut

OSHA Blade Guarding

Tiger-Tooth® Bi-Metal Blade

Coolant for Initial Start-Up

Specifications

Capacity	Round 13" Rectangular 13" x 18" 45° Angle 11" x 9-1/2"
Blade Size	1" x .035" x 12'6" (150")
Blade Speeds	Infinitely Variable 70-375 SFPM
Blade Guides	Carbide Guides with Rollers
Blade Tension	Manual Rite-Tension®
Electrical Options	115-208-230/60/1 208-230-460/60/3
Coolant System	Tank Capacity 8 Gallons Submersible Pump/3 GPM
Vise Control	Quick Acting/Manual Screw
Swivel Vise	To 45°
Feed Control	Variable Hydraulic/ Counterbalance Spring
Band Wheels	15" Diameter Cast Iron
Bed Height	35"
Floor Area	40"W x 84"L
Shipping Weight	955 Lbs.

Available Factory Installed Options

Flush Hose with 8.5 GPM Pump

Laser Line Pointer

Casters (Set of 4, 2 Locking)

NFPA Electrics (with Disconnect)

Work Light with Transformer

Stock Stand, 18"

5' Non-Powered Roller Conveyor

10' Non-Powered Conveyors

Please Contact Factory for Additional Options

Other Models in the 1318 Family

Model 1338 with 38" Width Capacity

Model 1316S Swivel Head Miter Saw to 60°

All Models Available with PLC Controlled Semi-Automatic Operation

The Model 1318-SA provides the strength and precision of our popular manual saw with the convenience of true semi-automatic operation. The factory programmed PLC manages the saw head and bed vise improving both safety and productivity.



Wellsaw® | 2829 N. Burdick Street | Kalamazoo, MI 49004 | Phone: 269-345-1132 | Fax: 269-345-0095 | Web: www.wellsaw.com